

**Product name:** Mat with Hidden Puzzle  
**Product code:** WRSP1K-XX-0300-000-00 black  
 WRSP1K-XX-030E-010-00 red  
 WRSP1K-XX-030E-020-00 green  
 WRSP1K-XX-030E-040-00 grey  
 WRSP1K-XX-030E-050-00 dark brown

-XX- code position is for product thickness



## PRODUCT MAIN DIMENSIONS

Thickness: 30, 40 mm

Length and width: 500 × 500 mm

Raster: 16 mm

*This image may slightly differ from the real product*

### Basic characteristics

<b>Material composition</b>	recycled black SBR granulate 1,0 -3,0 mm PU binder
<b>Colour**</b>	black, red, green, grey, dark brown
<b>Colour stability</b>	the colour may change when exposed to UV rays
<b>Chemical resistance</b>	do not use in the presence of oils, petroleum and its derivatives, strong acids and strong alkali
<b>REACH regulation (EC) 1907/2006 Substances of Very High Concern (SVHC)</b>	PASS (SVHC ≤ 0,1 % (w/w))
<b>Reaction to fire class</b>	E <sub>fl</sub> (according to EN 13501-1)
<b>Edges type</b>	bevelled edges
<b>Connection type</b>	hidden puzzle
<b>Recommended underlay</b>	concrete
<b>Thickness tolerance*</b>	± 1,5 mm
<b>Dimensional tolerance*</b>	±1,5%
<b>Weight tolerance</b>	± 0,2 kg
<b>Recycled content</b>	>90%

### Shipping and storage details

Length and width*	mm	500 × 500	
<b>Thickness*</b>	mm	<b>30</b>	<b>40</b>
Raster	mm	16	16
Weight	kg/pc	5,6	7,7
Pieces per m <sup>2</sup>	pc/m <sup>2</sup>	4	4
Pieces per pallet	pcs/pal	200	148
Pallet dimensions	mm	1100×1100	

*\*) The specified limit values are guaranteed only for the temperature range +23.0 +/- 5 °C, relative humidity 50.0 +/- 5 % according to EN 822, EN 823 and only if they are measured 24 hours after unpacking and relaxing of the products as described in Product installation requirements.*

*\*\*\*) Colour shades may vary between individual products* **Product installation requirements**

Before the actual installation, at first, it is necessary to unpack the products from the pallet, spread them out on the surface on which they are going to be installed. Then let them lay on the surface to obtain the same temperature and let them relax their dimensions at least for 24 hours. Only then it is possible to start the installation itself, for example by gluing.

### Use

Covering balconies, terraces, and relaxation areas.

### Revision

Rev. No.	Date	Description
-	-	-

This technical specification is issued in accordance with current knowledge and experiences of the manufacturer as well as external and internal testing. The manufacturer reserves the right to change these data. The products may only be used for the purpose for which they were manufactured and tested. Otherwise, the manufacturer does not guarantee the lifetime or properties of the products or any damage that may occur. Products must not be exposed to strong acids, bases, oxidizing agents or oils. For cleaning, water or a mild detergent solution can be used without use of abrasive agents or tools. At the end of their product life, they can be 100 % recycled or landfilled under No. 191 204 Plastics and Rubber according to the Waste Catalogue with accordance to applicable local and national regulations.